



PRODUCT SPECIFICATION

A. General Specification

Item		Specification	Condition
1	Model No.	DB9733	
2	Outline Dimension	97x94x33 mm	
3	Rated Voltage	DC 12V	
4	Starting Voltage	DC 6V	
5	Rated Current	0.86A	At Rated Voltage, 25°C, 65% RH
6	Power Consumption	10.32W	At Rated Voltage, 25°C, 65% RH
7	Speed	3600 RPM	At Rated Voltage, 25°C, 65% RH Free Air
8	Max. Airflow	26.0 CFM	At Rated Voltage AMCA Standard
9	Max. Static Pressure	25.4 mmH ₂ O	At Rated Current
10	Noise Level	51 dB(A)	At Rated Voltage Measured in a non-echo Chamber CNS 8753 Standard ISO 3744 Test Condition
11	Life	50,000/hrs at 25°C	MTBF (Mean Time Between Failures) Conf. Level 90%
12	No. of Blade		
13	No. of Pole		
14	Rotating Direction	Clockwise	
15	Tolerance	? 10%	At Rated Voltage
16	Weight	165g	
17	Motor Type	DC Brushless Fan Motor	
18.	Operating Voltage	6.0 ~13.0V	

B. Main Materials / Parts Specification

Materials / Parts		Specification
1	Plastic Material / Blade, Housing, Bobbin	UL 94V-0, P.B.T. + 30% GF Black
2	Bearing	Sleeve Bearing
3	Terminal	Lead wire (+Positive---Red , -Negative---Black)
4	Connector	

C. Safety Approvals :

Safety Approvals	File No.	Safety Approvals	File No.
CE			

D. Environmental Specification

Item		Specification / Condition
1	Operating Temp. Range	Temperature : -10°C ~ + 70°C Humidity : 35% - 85% RH
2	Storage Temperature	Temperature : -10°C ~+ 70°C Humidity : 35% - 85% RH
3	Humidity	Per MIL-STD 202F Method 103B; Life: 96 hours; Humidity : 95% RH; Temperature: 40 ? 2°C
4	Thermal Shock	Per MIL-STD 202F Method 107D, Condition D
5	Insulation Shock	UL: Class A
6	Packing Vibration Test	Packing Condition: X, Y, Z 3directions, 1.1 G load vibration test for 30 min.
7	Packing Shock Proof Test	1 corner, 3 edges, 6 faces natural drop from 60 cm high packing

E. Electrical Specification

Item		Specification/Condition
1	Insulation Resistance	10M Ω between frame and unshielded wire at 500VDC/min
2	Dielectric Strength	5mA Max. / Measured b/w lead wire (+) and frame at 500VAC/min
3	Locker Rotor Protection	a. No damage will be made for a continuous 72-hour rotation lock at rated voltage. b. Signal Alarm-Optional
4	Polarity Protection	Circuit is protected when Vcc & GND are exchanged.

F. Outline Dimension UNIT: mm

Unit:mm (inch)

